







Banjo Fittings

3118 Single Banjo, Male BSPP and Metric Thread

	Technical polymer, nickel-plated brass, NBR		ØD	C		E	F	G	H	L1	L2	kg
			3	M3x0.5 3118 03 09*		3	-	8.5	13	5	16	0.005
				M5x0.8 3118 03 19*		4	-	8.5	13	5	16	0.005
			4	M5x0.8 3118 04 19*		4	-	8.5	13	5	16.5	0.004
				G1/8 3118 04 10		4	13	8.5	17	7	18.5	0.012
				M5x0.8 3118 06 19*		4	-	10.5	13	7	18.5	0.004
			6	G1/8 3118 06 10		4	13	10.5	17	7	20	0.013
				G1/4 3118 06 13		5.5	17	10.5	21	9.5	22	0.023
				G1/8 3118 08 10		4	13	13.5	16.5	7	25	0.013
			8	G1/4 3118 08 13		5.5	17	13.5	21	9	27	0.024
				G3/8 3118 08 17		5.5	20	13.5	24.5	11	29	0.038
				G1/4 3118 10 13		5.5	17	16	21	9.5	29	0.025
			10	G3/8 3118 10 17		5.5	20	16	24.5	11	31	0.039
				G1/2 3118 10 21		8	25	19	27.5	13.5	36.5	0.083
			12	G3/8 3118 12 17		5.5	20	19	24.5	11	34.5	0.044
				G1/2 3118 12 21		8	25	19	27.5	13.5	36.5	0.074




*With screwdriver slot

3018 Single Banjo, Male BSPT Thread

	Technical polymer, nickel-plated brass, NBR		ØD	C		F	G	H	L	L1	kg
			4	R1/8 3018 04 10		13	8.5	18.5	18.5	7	0.015
			6	R1/8 3018 06 10		13	10.5	18.5	20	7	0.015
				R1/4 3018 06 13		17	10.5	22.5	22	9.5	0.029
				R1/8 3018 08 10		13	13.5	18.5	25	7	0.016
			8	R1/4 3018 08 13		17	13.5	22.5	27	9.5	0.030
				R3/8 3018 08 17		21	13.5	26.5	29	11	0.047
			10	R1/4 3018 10 13		17	16	22.5	29	9.5	0.032
				R3/8 3018 10 17		21	16	26.5	31	11	0.048
			12	R1/4 3018 12 13		21	19	26.5	34.5	11	0.052
				R3/8 3018 12 17		21	19	26.5	34.5	11	0.050
				R1/2 3018 12 21		25	19	30	37	13.5	0.086




Pre-coated thread

3124 Single Banjo, Male/Female BSPP and Metric Thread

	Technical polymer, nickel-plated brass, NBR		ØD	C		E	F	G	H	L	L1	kg
			4	M5x0.8 3124 04 19		4	8	8.5	19	16	5	0.006
				G1/8 3124 04 10		4	13	8.5	25.5	18.5	7	0.015
			6	G1/4 3124 06 13		5.5	17	10.5	33	22	9	0.030
			8	G3/8 3124 08 17		5.5	20	13.5	37.5	29	11	0.056




This product family was developed to allow assembly of a function fitting on a cylinder.

3149 Twin Banjo, Male BSPP and Metric Thread

	Technical polymer, nickel-plated brass, NBR		ØD	C		E	F	G	H	L	L1	N	kg
			4	M5x0.8 3149 04 19*		4	-	8.5	13	16	4.5	9	0.005
				G1/8 3149 04 10		4	13	10.5	16.5	18.5	7	11.5	0.018
			6	G1/8 3149 06 10		4	13	10.5	16.5	18.5	7	11.5	0.014
				G1/4 3149 06 13		5.5	17	13.5	21	27	9.5	14.5	0.035
			8	G1/4 3149 08 13		5.5	17	13.5	21	27	9.5	14.5	0.026
				G3/8 3149 08 17		5.5	20	16	24.5	31	11	17	0.053
			10	G3/8 3149 10 17		5.5	20	16	24.5	31	11	17	0.042

*With screwdriver slot

3119 Double Banjo, BSPP and Metric Thread

	Technical polymer, nickel-plated brass, NBR		ØD	C		E	F	G	H	L/2	kg
			4	M5x0.8 3119 04 19*		4	-	8.5	13	8	0.005
				G1/8 3119 04 10		4	13	11	17	20	0.021
			6	G1/8 3119 06 10		4	13	11	17	20	0.024
				G1/4 3119 06 13		5.5	17	13.5	21	26.5	0.031
			8	G1/4 3119 08 13		5.5	17	13.5	21	27	0.033
				G3/8 3119 08 17		5.5	20	16	24.5	30.5	0.053
			10	G3/8 3119 10 17		5.5	20	16	24.5	31	0.045

*With screwdriver slot