

State-of-the-Art Coupler Features Rigid Mounting and Connect/ Disconnect Under Pressure

The Pioneer 0312-001 rigid mount coupler features a patented design that permits connection while both the coupler and male tip are under pressure.

These couplers can be mounted directly to a valve or rigid tubing, eliminating the need for hose assemblies and break-away clamps.

- Easy push/pull connection and disconnection under system pressure.
- Enclosed outer housing prevents dust and dirt build up.
- This coupler accepts all Pioneer 8010 Series or ISO 5675 male tips.
- Environmentally friendly Chromium 6 Free plating for excellent corrosion resistance

Ordering Information

The 0312-001 is available in two packaging formats. Available in packages of five, or individually in the Valu-Pak clam shell for retail displays.

This coupler is the same product as **Kubota 3A111-82011**.

| Specifications | | | | | |
|----------------|----------------|--------------|--------------------------|--|--|
| Body Size | Part Number | Thread | Pressure Rating (psi) | | |
| 1/2 | 0312-001 | 7/8-14UNF-2B | 3000 PSI | | |
| 1/2 | VP0312-001-CS | 7/8-14UNF-2B | 3000 PSI | | |







ISO 5675 Univeral Male Tip for John Deere Equipment

The Pioneer tip has been the standard of the agriculture industry for over 60 years

The DR10008 male tip is manufactured to meet the original John Deere dimensional specifications, and has a slightly smaller hex size than a standard Pioneer tip.

- Meets all ISO 5675 dimensional specifications.
- Induction hardened ball locking groove to prevent brinelling and increase life.
- Shielded valve and valve stop eliminates flow checking.
- Leak-free poppet valve design
- Environmentally friendly Chromium 6 Free plating


Ordering Information

The DR10008 is available in two packaging formats. Available in bulk packages of 25, or individually in the Valu-Pak clam shell.

This male tip is the same product as John Deere AR94522.

| Specifications | | | | | |
|----------------|----------------|-------------------|--------------------------|--|--|
| Body Size | Part Number | Thread | Pressure Rating (psi) | | |
| 1/2 | DR10008 | 3/4-16 Female ORB | 3000 PSI | | |
| 1/2 | VPDR10008-CS | 3/4-16 Female ORB | 3000 PSI | | |









Eliminate the need for adapters for your 4000 Series John Deere tractors

The Pioneer DR10010 cartridge conversion kit is designed to convert John Deere 4000 Series tractors for use with ISO 5675 Pioneer style tips.

Upgrading your tractor with this conversion kit will eliminate the need for adapters. You will no longer need to adapt implements using the ISO male tips to the old style John Deere coupling interface.

- Easy push/pull operation
- Reduced pressure drop for longer system life
- Simple and fast installation
- Chromium 6 Free plating on all steel components for excellent corrosion resistance.

Ordering Information

This kit contains the components to convert two original John Deere couplings. (All of the components pictured above are included in the kit.)

This kit is the same product as John Deere RE206778.

| Specifications | | | | | | |
|----------------|----------------|--------|--------------------------|--|--|--|
| Body Size | Part Number | Thread | Pressure Rating (psi) | | | |
| 1/2 | DR10010 | Kit | 3000 PSI | | | |



