

















DIN - 公制

C9	A-92	0C	A-92	1C	A-92	D2	A-93
							
24°锥内螺纹 - 重系列 - O形圈 - 直接头		24°锥内螺纹 - 重系列 - O形圈 - 45°接头		24°锥内螺纹 - 重系列 - O形圈 - 90°接头		24°锥外螺纹-重系列 - 直接头	

法兰

15	A-93	4A	A-93	17	A-94	4F	A-94	19	A-94	4N	A-95
											
SAE 61系列 - 直法兰接头		SAE 61系列 - 直法兰接头 (5000 psi)		SAE 61系列 - 45° 法兰接头		SAE 61系列 - 45° 法兰接头 (5000 psi)		SAE 61系列 - 90° 法兰接头		SAE 61系列 - 90° 法兰接头 (5000 psi)	
6A	A-95	6F	A-96	6N	A-96						
											
SAE 62系列 - 直法兰接头		SAE 62系列 - 45° 法兰接头		SAE 62系列 - 90° 法兰接头							

ORFS

JS	A-97	J7	A-97	J9	A-97
					
ORFS内螺纹 - 直接头 - 加长型		ORFS内螺纹 - 45°接头		ORFS内螺纹-90° 接头 - 短型	

软管, 接头及设备

A

硬管接头及设备

B

快换接头

C


其他产品

D

1C973

公制24°锥内螺纹带O形圈 - 重系列 - 直接头

ISO 12151-2-SWS-S – DKOS




# 型号	螺纹 公制		软管内径 I.D.		A	B	W
	DN	inch	mm	mm	mm	mm	mm
1C973-20-12	20	M30x2	20	3/4	81	33	36
1C973-25-12	25	M36x2	20	3/4	79	31	46
1C973-25-16	25	M36x2	25	1	87	36	46
1C973-30-16	30	M42x2	25	1	87	36	50
1C973-30-20	30	M42x2	32	1-1/4	105	41	50
1C973-38-20	38	M52x2	32	1-1/4	103	39	60
1C973-38-24	38	M52x2	40	1-1/2	105	42	60

10C73

公制24°锥内螺纹带O形圈 - 重系列 - 45°接头

ISO 12151-2 – SWE 45°-S – DKOS 45°




# 型号	螺纹 公制		软管内径 I.D.		A	B	E	W
	DN	inch	mm	mm	mm	mm	mm	mm
10C73-20-12	20	M30x2	20	3/4	113	65	29	36
10C73-25-12	25	M36x2	20	3/4	113	65	29	46
10C73-30-16	30	M42x2	25	1	131	81	34	50
10C73-38-20	38	M52x2	32	1-1/4	164	100	38	60

11C73

公制24°锥内螺纹带O形圈 - 重系列 - 90°接头

ISO 12151-2-SWE-S – DKOS 90°



# 型号	螺纹 公制		软管内径 I.D.		A	B	E	W
	DN	inch	mm	mm	mm	mm	mm	mm
11C73-20-12	20	M30x2	20	3/4	107	59	62	36
11C73-25-12	25	M36x2	20	3/4	101	52	59	46
11C73-25-16	25	M36x2	25	1	117	66	70	46
11C73-30-16	30	M42x2	25	1	122	72	73	50
11C73-30-20	30	M42x2	32	1-1/4	138	73	74	50
11C73-38-20	38	M52x2	32	1-1/4	155	91	86	60


样本尺寸仅供参考, 请以实际产品尺寸为准。

1D273

公制24°锥外螺纹 - 重系列 - 直接头

ISO 12151-2-S-S - CES

# 型号					A mm	B mm	 H mm
	螺纹 公制		软管内径 I.D. DN	inch			
1D273-20-12	20	M30x2	20	3/4	84	35	30
1D273-25-12	25	M36x2	20	3/4	86	38	41
1D273-30-16	30	M42x2	25	1	94	43	46
1D273-38-20	38	M52x2	32	1-1/4	112	46	55




11573

SAE 61系列 - 直法兰接头

ISO 12151-3-S-L - SFL

# 型号				A mm	B mm	 F mm
		法兰 规格	软管内径 I.D. DN	inch		
11573-12-12		3/4	20	3/4	110	38
11573-16-12		1	20	3/4	91	45
11573-16-16		1	25	1	117	45




14A73


SAE 61系列 - 直法兰接头 (5000 psi)

ISO 12151-3-S-L - SFL

# 型号				A mm	B mm	 F mm
		法兰 规格	软管内径 I.D. DN	inch		
14A73-20-16		1-1/4	25	1	85	51
14A73-20-20		1-1/4	32	1-1/4	141	51
14A73-24-20		1-1/2	32	1-1/4	104	60
14A73-24-24		1-1/2	40	1-1/2	166	60
14A73-32-24		2	40	1-1/2	113	71
14A73-32-32		2	50	2	156	71



样本尺寸仅供参考，请以实际产品尺寸为准。




11773

SAE 61系列 - 45° 法兰接头

ISO 12151-3-E45-L - SFL45°

# 型号	法兰 规格	软管内径 I.D.		A mm	B mm	E mm	F mm
		DN	inch				
11773-12-12	3/4	20	3/4	119	71	27	38
11773-16-12	1	20	3/4	119	71	27	45
11773-16-16	1	25	1	127	77	32	45




14F73

SAE 61系列 - 45° 法兰接头 (5000 psi)

ISO 12151-3-E45-L - SFL45°

# 型号	法兰 规格	软管内径 I.D.		A mm	B mm	E mm	F mm
		DN	inch				
14F73-20-16	1-1/4	25	1	136	85	32	51
14F73-20-20	1-1/4	32	1-1/4	163	99	38	51
14F73-24-20	1-1/2	32	1-1/4	162	102	38	60
14F73-24-24	1-1/2	40	1-1/2	214	145	56	60
14F73-32-24	2	40	1-1/2	177	114	43	71
14F73-32-32	2	50	2	214	142	56	71



11973

SAE 61系列 - 90° 法兰接头

ISO 12151-3-E-L - SFL90°

# 型号	法兰 规格	软管内径 I.D.		A mm	B mm	E mm	F mm
		DN	inch				
11973-12-12	3/4	20	3/4	109	61	58	38
11973-16-12	1	20	3/4	102	54	58	45
11973-16-16	1	25	1	119	69	70	45


样本尺寸仅供参考, 请以实际产品尺寸为准。

14N73

SAE 61系列 - 90° 法兰接头 (5000 psi)

ISO 12151-3-E-L - SFL90°

# 型号	法兰 规格	软管内径 I.D.		A mm	B mm	E mm	F mm
		DN	inch				
14N73-20-16	1-1/4	25	1	128	78	68	51
14N73-20-20	1-1/4	32	1-1/4	155	91	90	51
14N73-24-20	1-1/2	32	1-1/4	155	91	90	60
14N73-24-24	1-1/2	40	1-1/2	166	107	104	60
14N73-32-24	2	40	1-1/2	166	103	92	71
14N73-32-32	2	50	2	220	148	133	71




16A73

SAE 62系列 - 直法兰接头

ISO 12151-3-S-S - SFS / 6000 psi

# 型号	法兰 规格	软管内径 I.D.		A mm	B mm	F mm
		DN	inch			
16A73-12-12	3/4	20	3/4	123	75	41
16A73-16-12	1	20	3/4	91	43	48
16A73-16-16	1	25	1	131	81	48
16A73-20-16	1-1/4	25	1	101	50	54
16A73-20-20	1-1/4	32	1-1/4	149	85	54
16A73-24-20	1-1/2	32	1-1/4	121	57	64
16A73-24-24	1-1/2	40	1-1/2	166	104	64
16A73-32-24	2	40	1-1/2	129	66	79
16A73-32-32	2	50	2	194	122	79



样本尺寸仅供参考，请以实际产品尺寸为准。

软管, 接头及设备
A

硬管接头及设备
B


快换接头
C

其他产品
D

16F73

SAE 62系列 - 45° 法兰接头

ISO 12151-3-E45-S - SFS45° / 6000 psi




# 型号	法兰 规格	软管内径 I.D.		A mm	B mm	E mm	F mm
		DN	inch				
16F73-12-12	3/4	20	3/4	110	62	26	41
16F73-16-12	1	20	3/4	120	72	26	48
16F73-16-16	1	25	1	129	79	32	48
16F73-20-16	1-1/4	25	1	128	78	32	54
16F73-20-20	1-1/4	32	1-1/4	163	99	38	54
16F73-24-20	1-1/2	32	1-1/4	163	99	38	64
16F73-24-24	1-1/2	40	1-1/2	178	119	44	64
16F73-32-32	2	50	2	214	145	56	79

16N73

SAE 62系列 - 90° 法兰接头

ISO 12151-3-E-S - SFS90° / 6000 psi



# 型号	法兰 规格	软管内径 I.D.		A mm	B mm	E mm	F mm
		DN	inch				
16N73-12-12	3/4	20	3/4	102	54	58	41
16N73-16-12	1	20	3/4	111	63	63	48
16N73-16-16	1	25	1	122	71	70	48
16N73-20-16	1-1/4	25	1	120	69	70	54
16N73-20-20	1-1/4	32	1-1/4	155	91	90	54
16N73-24-20	1-1/2	32	1-1/4	155	91	90	64
16N73-24-24	1-1/2	40	1-1/2	166	103	104	64
16N73-32-32	2	50	2	199	127	138	79


样本尺寸仅供参考, 请以实际产品尺寸为准。

1JS73

ORFS内螺纹 - 直接头 - 加长型

ISO 12151-1 - SWSB

# 型号	螺纹 UNF		软管内径 I.D.		A	B	H	W
			DN	inch	mm	mm	inch	inch
1JS73-12-12	3/4	1-3/16x12	20	3/4	94	48	1-1/8	1-3/8
1JS73-16-16	1	1-7/16x12	25	1	102	53	1-3/8	1-5/8
1JS73-20-20	1-1/4	1-11/16x12	32	1-1/4	132	69	1-3/4	1-7/8




1J773

ORFS内螺纹 - 45°接头

ISO 12151-1 - SWE45°

# 型号	螺纹 UNF		软管内径 I.D.		A	B	E	W
			DN	inch	mm	mm	mm	inch
1J773-12-12	3/4	1-3/16x12	20	3/4	104	58	21	1-3/8
1J773-16-16	1	1-7/16x12	25	1	119	70	24	1-5/8
1J773-20-20	1-1/4	1-11/16x12	32	1-1/4	147	84	25	1-7/8




1J973

ORFS内螺纹 - 90°接头 - 短型

ISO 12151-1 - SWES

# 型号	螺纹 UNF		软管内径 I.D.		A	B	E	W
			DN	inch	mm	mm	mm	inch
1J973-12-12	3/4	1-3/16x12	20	3/4	100	55	48	1-3/8
1J973-16-16	1	1-7/16x12	25	1	117	68	56	1-5/8
1J973-20-20	1-1/4	1-11/16x12	32	1-1/4	148	85	64	1-7/8



样本尺寸仅供参考，请以实际产品尺寸为准。