

Type “M” Adapters



The Type “M” adapters have a 60° female cone. Each Type “M” adapter is **rated for the full working pressure of the hose.**

Thread Sizes:

- 06 9/16"-18 UNF
- 08 3/4"-16 UNF
- 10 7/8"-14 UNF
- 11 1"-12 UNF
- 16 1-5/16"-12 UN




WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.


Type “M” Adapters

YAYA — Male Type “M” x Male Type “M”



Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Maximum Working Pressure	
#								
			inch	mm	inch	mm	psi	bar
YAYA-6-6C	9/16"-18 UNF	9/16"-18 UNF	1.38	35.05	0.63	16.00	60,000	4,140
YAYA-8-6C	3/4"-16 UNF	9/16"-18 UNF	1.63	41.40	0.75	19.05	30,000	2,070
YAYA-8-8C	3/4"-16 UNF	3/4"-16 UNF	1.75	44.45	0.75	19.05	30,000	2,070
YAYA-10-6C	7/8"-14 UNF	9/16"-18 UNF	1.88	47.75	1.00	25.40	60,000	4,140
YAYA-10-10C	7/8"-14 UNF	7/8"-14 UNF	2.00	50.80	1.00	25.40	50,000	3,445
YAYA-11-8C	1"-12 UNF	3/4"-16 UNF	1.88	47.75	1.00	25.40	30,000	2,070
YAYA-11-10C	1"-12 UNF	7/8"-14 UNF	1.98	50.29	1.00	25.40	30,000	2,070
YAYA-11-11C	1"-12 UNF	1"-12 UNF	1.88	47.75	1.00	25.40	30,000	2,070
YAYA-16-11C	1-5/16"-12 UN	1"-12 UNF	2.13	54.10	1.38	35.05	20,000	1,380
YAYA-16-16C	1-5/16"-12 UN	1-5/16"-12 UN	2.13	54.10	1.38	35.05	20,000	1,380

YAY6 — Male Type “M” x Male High Pressure




Part Number	T1 Thread Size	T2 Thread Size	Nominal Tube Size	A Overall Length		H Hex		Maximum Working Pressure	
#									
				inch	mm	inch	mm	psi	bar
YAY6-6-4C	9/16"-18 UNF	9/16"-18 UNF	1/4" HP	1.53	38.86	0.63	16.00	60,000	4,140
YAY6-6-6C	9/16"-18 UNF	3/4"-16 UNF	3/8" HP	1.75	44.45	0.75	19.05	60,000	4,140
YAY6-6-9C	9/16"-18 UNF	1-1/8"-12 UNF	9/16" HP	2.00	50.80	1.13	28.70	60,000	4,140
YAY6-8-6C	3/4"-16 UNF	3/4"-16 UNF	3/8" HP	2.00	50.80	0.75	19.05	30,000	2,070
YAY6-8-9C	3/4"-16 UNF	1-1/8"-12 UNF	9/16" HP	2.25	57.15	1.13	28.70	30,000	2,070
YAY6-10-6C	7/8"-14 UNF	3/4"-16 UNF	3/8" HP	2.25	57.15	1.00	25.40	60,000	4,140
YAY6-10-9C	7/8"-14 UNF	1-1/8"-12 UNF	9/16" HP	2.38	60.45	1.13	28.70	60,000	4,140
YAY6-11-9C	1"-12 UNF	1-1/8"-12 UNF	9/16" HP	2.25	57.15	1.13	28.70	30,000	2,070

WARNING
 This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
 For more information go to www.P65Warnings.ca.gov.


Type "M" Adapters

YAY5 — Male Type "M" x Male Medium Pressure



Part Number	T1 Thread Size	T2 Thread Size	Nominal Tube Size	A Overall Length		H Hex		Maximum Working Pressure	
#									
				inch	mm	inch	mm	psi	bar
YAY5-6-4C	9/16"-18 UNF	7/16"-20 UNF	1/4" MP	1.56	39.62	0.63	16.00	20,000	1,380
YAY5-6-6C	9/16"-18 UNF	9/16"-18 UNF	3/8" MP	1.63	41.40	0.63	16.00	20,000	1,380
YAY5-6-9C	9/16"-18 UNF	13/16"-16 UN	9/16" MP	2.00	50.80	0.88	22.35	20,000	1,380
YAY5-6-12C	9/16"-18 UNF	3/4"-14 NPS	3/4" MP	2.32	58.93	1.13	28.70	20,000	1,380
YAY5-8-4C	3/4"-16 UNF	7/16"-20 UNF	1/4" MP	1.68	42.67	0.75	19.05	20,000	1,380
YAY5-8-6C	3/4"-16 UNF	9/16"-18 UNF	3/8" MP	1.88	47.75	0.75	19.05	20,000	1,380
YAY5-8-9C	3/4"-16 UNF	13/16"-16 UN	9/16" MP	2.20	55.88	0.88	22.35	20,000	1,380
YAY5-8-12C	3/4"-16 UNF	3/4"-14 NPS	3/4" MP	2.44	61.98	1.13	28.70	20,000	1,380
YAY5-11-4C	1"-12 UNF	7/16"-20 UNF	1/4" MP	1.94	49.28	1.00	25.40	20,000	1,380
YAY5-11-6C	1"-12 UNF	9/16"-18 UNF	3/8" MP	2.00	50.80	1.00	25.40	20,000	1,380
YAY5-11-9C	1"-12 UNF	13/16"-16 UN	9/16" MP	2.25	57.15	1.00	25.40	20,000	1,380
YAY5-11-12C	1"-12 UNF	3/4"-14 NPS	3/4" MP	2.44	61.98	1.13	28.70	20,000	1,380
YAY5-16-9C	1-5/16"-12 UN	13/16"-16 UN	9/16" MP	2.50	63.50	1.38	35.05	20,000	1,380
YAY5-16-12C	1-5/16"-12 UN	3/4"-14 NPS	3/4" MP	2.70	68.58	1.38	35.05	20,000	1,380

YAD9 — Male Type "M" x Male BSP



Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Maximum Working Pressure	
#								
			inch	mm	inch	mm	psi	bar
YAD9-6-4C	9/16"-18 UNF	G 1/4"-19	1.36	34.54	0.75	19.05	30,000	2,070
YAD9-6-6C*	9/16"-18 UNF	G 3/8"-19	1.36	34.54	0.875	22.23	30,000	2,070
YAD9-6-8C*	9/16"-18 UNF	G 1/2"-14	1.54	39.12	1.00	25.40	30,000	2,070

*Non-standard part - may require longer lead time




WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Type “M” Adapters


Plugs

Part Number	T1 Thread Size	A Overall Length		H Hex		Maximum Working Pressure	
		inch	mm	inch	mm	psi	bar
#							
YA6C-PLUG	9/16"-18 UNF	2.07	52.58	0.75	19.05	60,000	4,140
YA8C-PLUG	3/4"-16 UNF	2.13	54.10	1.00	25.40	30,000	2,070
YA11C-PLUG	1"-12 UNF	1.25	31.75	1.00	25.40	30,000	2,070
YA16C-PLUG	1-5/16"-12 UN	2.63	66.80	1.38	35.05	20,000	1,380




Caps

Part Number	T1 Thread Size	A Overall Length		H Hex		Maximum Working Pressure	
		inch	mm	inch	mm	psi	bar
#							
AY6C-CAP	9/16"-18 UNF	0.85	21.59	0.69	17.53	60,000	4,140
AY8C-CAP	3/4"-16 UNF	0.91	23.11	1.00	25.40	30,000	2,070
AY11C-CAP	1"-12 UNF	1.31	33.27	1.25	31.75	30,000	2,070
AY16C-CAP	1-5/16"-12 UN	1.20	30.48	1.50	38.10	20,000	1,380



Torpedos

Part Number	T1 Thread Size	T2 Thread Size	A Overall Length		H Hex		Maximum Working Pressure	
			inch	mm	inch	mm	psi	bar
#								
YAY1-8-16C	3/4"-16 UNF	1"-14 LH	3.56	90.42	1.13	28.70	20,000	1,380
YAY2-8-16C	3/4"-16 UNF	1"-14 LH	3.56	90.42	1.38	35.05	20,000	1,380
YAY1-11-16C	1"-12 UNF	1"-14 LH	3.56	90.42	1.13	28.70	20,000	1,380
YAY2-11-16C	1"-12 UNF	1"-14 LH	3.56	90.42	1.38	35.05	20,000	1,380
YAY1-16-16C	1-5/16"-12 UN	1"-14 LH	3.70	93.98	1.38	35.05	20,000	1,380
YAY2-16-16C	1-5/16"-12 UN	1"-14 LH	3.70	93.98	1.38	35.05	20,000	1,380



WARNING

This product can expose you to chemicals including Lead, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.